



Dry



Wet



Heat



Oily



Cold



Chemical



TG5060

A flexible, highly dextrous double dip X-Dura nitrile waterproof glove with an extended cuff providing additional cut protection. Ideal for outdoor construction and civil engineering offering oil and water resistance.

Key Features

- Full dip waterproof glove with extra nitrile foam palm for enhanced grip in wet and oily conditions
- Generous knit wrist for comfort and to ensure a secure fit and protects hand from dirt and debris
- Excellent abrasion and tear resistance

Ideal for

- Construction and Utility
- Engineering and Manufacturing
- Oil and Gas
- Waste, Recycling and Local Authority
- Warehousing and Logistics

Sizes:	7-11	Gauge:	15gg
Liner:	Polyamide	Coating:	X-Dura Nitrile
No/Bag:	10	No/Carton:	100

TG5060

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
15 gauge

Liner Type
Polyamide

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
Double dipped X-Dura Nitrile

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 450mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.