



Dry



Wet



Heat



Oily



Cold



Chemical



TG5570

Cut F thermal glove full dip flat latex and black sandy palm dip latex. Thermal and water resistant, even on the wrist, with a single layer liner for maximum dexterity and comfort.

Key Features

- Highest level of cut protection according to EN388:2016
- Impressive comfort flexibility
- Seamless knitted 10 gauge liner for enhanced breathability
- Great dexterity and high cut level for outdoor environment
- Water resistant and thermal - perfect for winter weather

Ideal for

- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Waste, recycling & local authority
- Warehousing & logistics

Sizes:	7-11	Gauge:	10gg
Liner:	HPPE/Acrylic, Steel, Nylon, Glass, Spandex	Coating:	X-Dura Latex
No/Bag:	10	No/Carton:	100

TG5570

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
10 gauge

Liner Type
HPPE/Acrylic/Steel/Nylon/Glass/Spandex

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Latex

Dip Application
Palm dip

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
320mm x 700mm x 450mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.